

EMISSION CONTROL

0304C-02

SERVICE DATA

2AZ-FE

A/F sensor (bank 1 sensor 1) resistance	at 20°C (68°F) at 800°C (1,472°F)	0.8 to 1.4 Ω 1.8 to 3.2 Ω
Oxygen sensor (bank 1 sensor 2) resistance	at 20°C (68°F) at 800°C (1,472°F)	11 to 16 Ω 23 to 32 Ω
VSV for EVAP resistance	at 20°C (68°F)	26 to 30 Ω

3MZ-FE

A/F sensor (bank 1 sensor 1) resistance	at 20°C (68°F) at 800°C (1,472°F)	0.8 to 1.4 Ω 1.8 to 3.2 Ω
A/F sensor (bank 2 sensor 1) resistance	at 20°C (68°F) at 800°C (1,472°F)	0.8 to 1.4 Ω 1.8 to 3.2 Ω
Oxygen sensor (bank 1 sensor 2) resistance	at 20°C (68°F) at 800°C (1,472°F)	11 to 16 Ω 23 to 32 Ω
Oxygen sensor (bank 2 sensor 2) resistance	at 20°C (68°F) at 800°C (1,472°F)	11 to 16 Ω 23 to 32 Ω
VSV for CCV resistance	at 20°C (68°F) at 100°C (212°F)	25 to 30 Ω 32 to 40 Ω
VSV for EVAP resistance	at 20°C (68°F)	26 to 30 Ω