

ENGINE HOOD/DOOR

TORQUE SPECIFICATION

03051-03

Part Tightened	N-m	kgf-cm	ft-lbf
HOOD	-	-	-
Hood x Hood hinge	13	130	10
Hood lock x Body	7.0	71	62 in.·lbf
FRONT DOOR	-	-	-
Door hinge x Body	23	235	17
Door hinge x Door panel	27	235	17
Door lock x Door panel for 3 torx screw	5.0	50	45 in.·lbf
Door lock x Door panel for screw	5.5	56	49 in.·lbf
Door lock striker x Body	23	235	17
Handle frame x Door panel	4.0	41	35 in.·lbf
Outside handle cover x Door panel	4.0	41	35 in.·lbf
Window regulator x Motor	5.4	55	48 in.·lbf
Window regulator x Door panel	11	112	8.0
REAR DOOR	-	-	-
Door hinge x Body for Lower hinge	26	265	19
Door hinge x Body for Upper hinge	23	235	17
Door hinge x Door panel	26	265	19
Door lock x Door panel	5.0	50	44 in.·lbf
Door lock x Door panel	5.5	56	49 in.·lbf
Door lock striker x Body	23	235	17
Handle frame x Door panel	4.0	41	35 in.·lbf
Outside handle cover x Door panel	4.0	41	35 in.·lbf
Window regulator x Door panel	11	112	8.0
Window regulator x Motor	5.4	55	48 in.·lbf
BACK DOOR	-	-	-
Door lock x Door panel	12.5	128	9.0
Door lock striker x Body	23	235	17
Hinge x Body	19.5	199	14
Lock cylinder x Door panel	5.5	56	49 in.·lbf
Outside handle x Door panel	5.5	56	49 in.·lbf
BACK DOOR STAY	-	-	-
Back door Stay x Body	8.0	82	71 in.·lbf
Back door Stay x Door panel	8.0	82	71 in.·lbf