

## TORQUE SPECIFICATION

Part Tightened	N·m	kgf·cm	ft·lbf
Bleeder plug	8.3	85	73 in·lbf
Brake booster clevis lock nut	26	265	19
Stop lamp switch assy lock nut	17	173	13
Brake pedal support sub-assy x Brake pedal sub-assy	37	375	27
Brake master cylinder x Brake tube	15	155	11
Brake booster x Body	13	130	9
Brake pedal support sub-assy x Body	13	130	9
Brake pedal support sub-assy x Instrument panel reinforcement	20	204	15
Brake master cylinder x Brake booster	13	127	9
Wheel nut	103	1,050	76
Front brake cylinder mounting x Steering knuckle	104	1,061	77
Front brake cylinder x Front brake cylinder mounting	34	350	25
Front disc brake cylinder x Flexible hose	29	300	21
Rear disc brake cylinder mounting x Rear axle	78	799	58
Rear brake cylinder x Rear brake cylinder mounting	43	440	32
Rear disc brake cylinder x Flexible hose	29	300	21
Front speed sensor x Steering knuckle	8.0	82	71 in·lbf
Front speed sensor wire harness clamp x Shock absorber	29	300	22
Front speed sensor wire harness clamp x Body	5.0	51	44 in·lbf
Rear speed sensor x Rear axle 4WD:	8.0	82	71 in·lbf
Rear speed sensor wire harness clamp x Body	5.0	51	44 in·lbf
Brake actuator with bracket x Body	19	194	14
Brake actuator assy x Brake tube	15	155	11
Brake actuator x Brake actuator bracket assy	5.4	55	48 in·lbf
Yawrate sensor x Body	14	143	10