

TORQUE SPECIFICATION

Part Tightened		N·m	kgf·cm	ft·lbf
Hub nut		103	1,050	76
Tie rod adjusting tube set nut		56	570	41
Shock absorber with coil spring x Rear axle carrier		180	1,840	133
Shock absorber with coil spring x Body		58	590	43
Support assy rear suspension x Shock absorber piston rod		49	500	36
Flexible hose set bolt		19	192	14
Skid control sensor wire set bolt		5.0	51	44 in.·lbf
Speed sensor set bolt		8.0	82	71 in.·lbf
Speed sensor wire set bolt		5.0	51	44 in.·lbf
Strut rod x Body		80	816	59
Strut rod x Rear axle carrier		80	816	59
Parking brake cable set bolt		39	400	29
Parking brake cable set nut		6.0	61	53 in.·lbf
Rear suspension member (4WD) set nut	Front side	115	1,170	85
	Rear side	181	1,850	134
Rear suspension arm assy No.1 x Rear suspension member	FF	120	1,220	89
	4WD	80	816	59
Rear suspension arm assy No.1 x Rear axle carrier	FF	112	1,140	83
	4WD	112	1,140	83
Rear suspension arm assy No.2 x Rear suspension member	FF	120	1,220	89
	4WD	100	1,020	74
Rear suspension arm assy No.2 x Rear axle carrier	FF	112	1,140	83
	4WD	112	1,140	83
Stabilizer link set nut		39	400	29
Stabilizer bar bracket set bolt (FF)		19	194	14
Stabilizer bar set bolt (4WD)	Left side	54	550	40
	Right side	19	194	14